USB-C Faceplate

USB Type C Faceplate

WirelessKable Inc.

Proudly Made in CANDA with domestic and imported parts

Document Revision: A



SPECIFICATIONS

Input Voltage	USB-C PD with Data Passthrough	
Input Current	5.0 A Max	
Output Voltage	USB-C PD with Data Passthrough	
Output Current	5.0 A Max	
USB Connector	Secure USB type C to USB-C	
Weight	0.055 lb (25 g)	
Dimensions	Faceplate 1.12" W / 1.12" L / 0.75" H Cut-out 1" W / 1" L Product 1.12" W / 1.12" L / 0.97" H	
Mounting	Front with Spring Clips	
Certification	RTCA DO-160G Compliance w ith EN50155 Design as per USB PD rev 2.0	
Applications	Aerospace, Railw ays, Automotive, Military	
Appearance	Standard - Gray Anodized Optional plating on demand	
Used With	551-5227-001 - USB-C AC20 Mode 1 551-5227-003 - USB-C AC20 Mode 3 551-5237-001 - USB AC65 Mode 1 551-5237-003 - USB AC65 Mode 3	
Mating Cycles	50,000	

ORDERING INFORMATION

Part Number	551-5527-001
Description	USB-C Faceplate
	<u> </u>
4	
Ū	



DESCRIPTION

The product is a USB-C pass-through passive device. Is used as a small footprint USB-C external connector when used with USB-C Converters or in conjunction with USB-C to HDMI Converter.

The faceplate can be plated for special needs.

FEATURES

- A very small footprint
- Lightweight
- Platable Faceplate
- Cost-effective solution